

**AMENDMENTS TO THE CLAIMS:**

This listing of claims will replace all prior versions and listings of claims in the application:

B1

1. (Currently Amended) Elevator emergency stop device for an elevator cage guided on a guide rail, comprising:

a ~~guide rail guiding an elevator cage~~; and

a wedge-shaped element that effects an emergency stop of said elevator cage by frictional force by means of a contact face of a sliding part thereof being pressed against said guide rail,

wherein said wedge-shaped element comprises a mechanism whereby a dimension of said wedge-shaped element in the direction perpendicular ~~with respect to faces along which said guide rail and said sliding part slide~~ to said contact face is changed in accordance with braking force to maintain the braking force at a substantially constant level.

2. (Original) Elevator emergency stop device according to claim 1,

wherein said wedge-shaped element comprises:

a fixed part having an outside inclined face part of said wedge-shaped element;

and

a wedge-shaped moveable part having said sliding part;

said moveable part being moveable along an inside inclined face part of said fixed part and an upper part thereof being engaged with said fixed part by means of a resilient element.

FINNEGAN  
HENDERSON  
FARABOW  
GARRETT &  
DUNNER LLP

1300 I Street, NW  
Washington, DC 20005  
202.408.4000  
Fax 202.408.4400  
www.finnegan.com

3. (Original) Elevator emergency stop device according to claim 2,

wherein in said wedge-shaped element said fixed part and said resilient element, and said resilient element and said moveable part are engaged by means of respective sliding elements between said resilient element and said moveable element and between said resilient element and said fixed element.

4. (Original) Elevator emergency stop device according to claim 2 or 3,

wherein in said resilient element a relationship between a load and a flexure is such that said flexure is small or zero up to a prescribed load and above said prescribed load said relationship between said load and said flexure is a practically proportional relationship.

5. (Original) Emergency stop device according to claim 4,

wherein said resilient element comprises a piston in which is sealed gas that is given an initial pressure.

FINNEGAN  
HENDERSON  
FARABOW  
GARRETT &  
DUNNER LLP

1300 I Street, NW  
Washington, DC 20005  
202.408.4000  
Fax 202.408.4400  
www.finnegan.com